

WorkCentre® 7425 / 7428 / 7435

Color Multifunction Printer



WorkCentre 7425
shown with Work Surface and
Three Tray options.



WorkCentre 7428
shown with Work Surface,
High-Capacity Tandem Tray
and Office Finisher LX with
Booklet Maker options.



WorkCentre 7435
shown with Work Surface,
High-Capacity Tandem Tray,
High Capacity Feeder and
Professional Finisher options.

	WorkCentre 7425	WorkCentre 7428	WorkCentre 7435
Output Speed – Printing and Copying			
Black and white	Up to 25 ppm (pages per minute) 8.5 x 11 in. (A4/210 x 297 mm) LEF Up to 16 ppm 8.5 x 14 in. (216 x 356 mm) Up to 14 ppm 11 x 17 in. (A3/297 x 420 mm)	Up to 28 ppm 8.5 x 11 in. (A4/210 x 297 mm) LEF Up to 18 ppm 8.5 x 14 in. (216 x 356 mm) Up to 16 ppm 11 x 17 in. (A3/297 x 420 mm)	Up to 35 ppm 8.5 x 11 in. (A4/210 x 297 mm) LEF Up to 23 ppm 8.5 x 14 in. (216 x 356 mm) Up to 20 ppm 11 x 17 in. (A3/297 x 420 mm)
Color	Up to 20 ppm 8.5 x 11 in. (A4/210 x 297 mm) Up to 13 ppm 8.5 x 14 in. (216 x 356 mm) Up to 11 ppm 11 x 17 in. (A3/297 x 420 mm)	Up to 28 ppm 8.5 x 11 in. (A4/210 x 297 mm) Up to 18 ppm 8.5 x 14 in. (216 x 356 mm) Up to 16 ppm 11 x 17 in. (A3/297 x 420 mm)	Up to 35 ppm 8.5 x 11 in. (A4/210 x 297 mm) Up to 23 ppm 8.5 x 14 in. (216 x 356 mm) Up to 20 ppm 11 x 17 in. (A3/297 x 420 mm)
First-Page-Out Time			
Copy – Black and white	As fast as 6.7 seconds	As fast as 5.0 seconds	As fast as 5.0 seconds
Copy – Color	As fast as 8.7 seconds	As fast as 6.4 seconds	As fast as 6.4 seconds
Paper Handling			
Paper Handling – Duplex Automatic Document Feeder			
Capacity	75 sheets (based on 20 lb Bond/80 gsm paper)		
Speed	50 images per minute black and white/45 images per minute color (Letter/A4 long edge feed (LEF))		
Sizes	5.5 x 8.5 in. (A5/148 x 210 mm) to 11 x 17 in. (A3/297 x 420 mm)		
Weights	16 to 32 lb Bond / 60 to 120 gsm		

WorkCentre 7425 / 7428 / 7435

Paper Handling – Bypass Tray	
Capacity*	100 sheets
Sizes	4.13 x 5.83 in. (A6/105 x 148 mm) to 12 x 18 in. (SRA3/320 x 450 mm)
Weights	16 lb Bond to 100 lb Cover / 55 to 280 gsm
Types	Same as front-loading trays plus envelopes
Paper Handling – Main Tray 1 (Standard)	
Capacity*	520 sheets
Sizes	User adjustable from 5.5 x 7.2 in. (139.7 x 182 mm) to 11 x 17 in. (A3/297 x 420 mm)
Weights	16 lb Bond to 100 lb Cover / 55 to 280 gsm
Types	Plain Paper Recycled Bond Custom Type 1 through 5 Lightweight Heavyweight Extra Heavyweight Transparency Gloss Heavyweight Gloss Extra Heavyweight Gloss Labels Punched Letterhead Pre-printed
Envelope Tray (Optional – replaces Tray 1)	
Capacity*	Up to 60 envelopes
Sizes	#10 Commercial (9.25 x 4.125 in.), Monarch, DL, C5, custom, Large U.S. Postcard, A6
Weights	75 to 90 gsm
Paper Handling – Input Tray Options - Three Tray Option	
Tray 2, Tray 3, Tray 4	520 sheets each
Sizes	User adjustable from 5.5 x 7.2 in. (139.7 x 182 mm) to 12 x 18 in. (SRA3/320 x 450 mm)
Weights	16 lb Bond to 100 lb Cover / 60 to 280 gsm
Types	Plain Paper Recycled Bond Custom Type 1 through 5 Lightweight Heavyweight Extra Heavyweight Transparency Gloss Heavyweight Gloss Extra Heavyweight Gloss Labels Punched Letterhead Pre-printed Envelopes

* Paper capacities are based on 20 lb/80 gsm stock; capacities will vary with different weight stocks.

WorkCentre 7425 / 7428 / 7435

Total Capacity*	2,180 sheets (Includes Tray 1, Three Tray option and Bypass Tray)
Paper Handling – Input Tray Options - High-Capacity Tandem Tray Option	
Tray 2	520 sheets
Sizes	User adjustable from 5.5 x 7.2 in. (139.7 x 182 mm) to 12 x 18 in. (SRA3/320 x 450 mm)
Tray 3 and Tray 4	2,000 sheets total
Sizes	8.5 x 11 in., B5, A4
Weights	16 lb Bond to 100 lb Cover / 60 to 280 gsm
Types	Plain Paper Recycled Bond Custom Type 1 through 5 Lightweight Heavyweight Extra Heavyweight Transparency Gloss Heavyweight Gloss Extra Heavyweight Gloss Labels Punched Letterhead Pre-printed Envelopes
Total Capacity*	3,140 sheets (Includes Tray 1, High-Capacity Tandem Tray option and Bypass Tray)
Paper Handling – High-Capacity Feeder (HCF)	
Capacity	2,000 sheets of 20 lb Bond (75 gsm)
Sizes	8.5 x 11 in. LEF (A4/210 x 297 mm)
Weights	16 lb Bond to 80 lb Cover / 55 to 216 gsm
Total Capacity*	5,140 sheets with High Capacity Tandem Tray option – 4,180 sheets with Three Tray option
Output – Standard	
Stacking Trays*	Dual Offset Catch Tray – up to 250 sheets each Face up Tray – up to 100 sheets
Sizes	5.5 x 8.5 in. (A5/148 x 210 mm) to 12 x 18 in. (SRA3/320 x 450 mm)
Weights	16 lb Bond to 140 lb Index / 60 to 256 gsm
Output – Integrated Office Finisher Option	
Stacking Tray	500 sheets of 20 lb Bond (80 gsm) 8.5 x 11 in./A4 or 250 sheets of 20 lb Bond (80 gsm) 11 x 17 in./A3
Sizes	8 x 10 in. / B5 to 11 x 17 in. / A3
Weights	16 lb Bond to 80 lb Cover / 60 to 220 gsm
Stapling	Single Auto stapling (50 sheets maximum less than 90 gsm or (2) 220 gsm covers) Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported

* Paper capacities are based on 20 lb/80 gsm stock; capacities will vary with different weight stocks.

WorkCentre 7425 / 7428 / 7435

Output – Office Finisher LX Option	
Stacking Tray	2,000 sheets unstapled or 1,000 sheets single staple or 750 sheets dual staple (24 lb Bond / 90 gsm)
Sizes	8 x 10 in. / B5 to 11 x 17 in. / A3
Weights	16 lb Bond to 80 lb Cover / 60 to 220 gsm
Stapling	Single and dual Auto stapling (50 sheets maximum less than 90 gsm) Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
Output – Optional Hole Punch for Office Finisher LX	
North America	3-hole punch 2-hole Legal punch
Europe	2-hole punch 4-hole punch
Output – Optional Booklet Maker (Score/Crease, Saddle-stitch Staple) for Office Finisher LX	
Capacity	40 booklets (1-15 sheets per booklet – 80 gsm or less; 2-10 sheets per booklet – over 80 gsm)
Sizes	Letter – 8.5 x 11 in. (A4/210 x 297 mm) Legal – 8.5 x 14 in. (216 x 356 mm) Ledger – 11 x 17 in. (A3/297 x 420 mm)
Saddle-stitch Stapling	2-15 sheets / 8 – 60 page booklet 16 lb Bond to 24 lb Bond / 55 to 90 gsm
Score/Crease	1-15 sheets / unstapled
Output – Professional Finisher Option	
Top Tray	500 sheets
Stacking Stapling Tray	1,500 sheets
Sizes	8 x 10 in./B5 to 12 x 18 in./SRA3
Weights	16 lb Bond to 80 lb Cover / 60 to 220 gsm
Stapling	Single Auto stapling (50 sheets maximum) – 24 lb/90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
Booklets - Booklet Tray	Saddle-stitch up to 15 sheets (One 60 lb cover/169 gsm plus fourteen 24 lb Bond/90 gsm sheets) V-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4, SRA3 supported
Hole Punch	North America: 2–3 Hole Punch Europe: 2–4 Hole Punch, Swedish Hole Punch
Copy Specifications	
Document Scanner	Duplex Automatic Document Feeder with 75-sheet capacity (based on 80 gsm paper)
Sides (input:output)	1:1, 1:2, 2:2 and 2:1
Quantity	1 to 999
Resolution	600 x 600 dpi
Concurrency	Concurrent scan, print, fax

WorkCentre 7425 / 7428 / 7435

Digital Imaging	<p>Enhanced Gloss Level Auto color Auto rotation Image shift Edge erase Auto centering Original type selection (photo and text, photo, text, map) with subtypes Lighter/darker Background suppression Auto and manual contrast Sharpness Color balance, color shift and saturation</p>
Reduction/Enlargement	<p>Variable zoom from 25 % to 400 % in 1 % increments Anamorphic zoom Six user-programmable percentages</p>
Special Features	<p>Auto paper select Auto reduction/enlargement to fit selected paper size Auto registration Auto tray switching Automatic job recovery Auto color selection Area Designation Poster mode Watermark Secure Watermark (requires Secure Watermark Kit option) Annotation Single/Dual color Copy calibration Booklet creation Multi-up – 2, 4 or 8 up Repeat Image Transparency dividers Negative image Mirror image Covers insertion (front only, front and back, back only, blank or printed) Build Job (enables special programming for different pages in one document – can be used for inserts, different paper sources and mixing input from the document glass and the document feeder) Store and recall job programming Job interrupt Book copying Sample job Mixed-size originals Hole Punch (requires Professional Finisher or Office Finisher LX) V-Folding (requires Professional Finisher) Saddle-stitch booklets (requires Professional Finisher or Office Finisher LX) Stapling (single/dual/quad) (quad requires Professional Finisher) ID Card Copy</p>
Foreign Device Interface	<p>Interface to third-party access control devices, coin machines and card readers Supports a variety of vending stations available through the Xerox Custom Application Service</p>
Print Specifications	
System	
Memory	1.5 GB
System Disk	Minimum 40 GB

WorkCentre 7425 / 7428 / 7435

Network Printing – Network Controller	
Processor	667 MHz
Printer Languages (auto sensing/switching)	Adobe® Postscript® 3™ TIFF PCL® 5c PS-PDF: v1.3 PCL® 6 HP-GL2™ XPS®
Network Printing – Resolution	
	Print Engine: 1200 x 2400 dpi
Network Printing – Printing Features	
Features	Enhanced Gloss Level Print Calibration Secure Print Delay Print (specific time) Sample Set Booklet creation Cover selection Inserts and exception pages Store File in Folder Paper selection by attribute N-up Saddle-stitch booklet making (requires Professional Finisher or Office Finisher LX) Hole Punch (requires Professional Finisher or Office Finisher LX) Booklet Fold / V Folding (requires Professional Finisher or Office Finisher LX) Watermark Secure Watermark (requires optional Secure Watermark Kit) Fit to new paper size Transparency Separators Banner Sheet enable/disable Output tray selection Image Quality Draft Mode Store and Recall driver settings Reduce/enlarge Mirror image Margins Bi-Directional status Two sided printing Scaling Overlays Print to Fax (requires optional Fax Kit)
Connectivity	Ethernet 10/100BaseTX High speed USB 2.0 printer port Wireless Ethernet (IEEE 802.11b) via third-party adapters Parallel Port (optional)
Operating Systems	Microsoft® Windows® XP® 32-bit, XP 64-bit, Windows Server 2003 32-bit, Windows Server 2003 64-bit, Windows Vista 32-bit, Windows Vista 64-bit Mac OS® 10.3 and above AIX 5iV5.3 HP UX 11.0, 11i v2 Solaris 8, 9, 10 Linux® FedoraCore 1, 5 RedHat Enterprise Linux 4 SUSE 10.x

Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6 Netware: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP and NetBEUI (All protocols not in use can be disabled)		
Administrative Protocols	DHCP, BOOTP, SNMP, WINS, DDNS, SLP® v2, HTTP, RARP, DHCP Autonet, SSL		
Fonts	Postscript 3: 136 Type 1 fonts, 2 Multiple Master fonts PCL: 81 scalable fonts, line printer bitmap font		
Printer Drivers	Environment	PCL5c and PCL 6	PostScript
Vista XPS (mini driver available)	Windows 2003/XP 32 Bit Windows 2003/XP 64 Bit Windows Vista/Vista 32 Bit Windows Vista/Vista 64 Bit (Microsoft certified)	Bidirectional with user-selectable interface (standard** and enhanced*)	Bidirectional with user-selectable interface (standard** and enhanced*)
	Macintosh® OS 10.3.0 and above	N/A	Enhanced PPD file
	UNIX	N/A	Bidirectional with Xerox Custom Graphical User Interface
Xerox Mobile Express Driver (X-MED)	<p>Makes it easy for mobile users to find, use and manage Xerox and non-Xerox devices in every new location. Plug into a new network, and X-MED automatically discovers available printers and provides status and capability information. Save a list of “favorite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.</p> <ul style="list-style-type: none"> • Printers are automatically discovered • Printer list can be managed based on location • Gives Bi-directional feedback device status, supplies, queue management 		
Xerox Global Print Driver (X-GPD)	<p>A truly universal print driver that lets IT administrators install, upgrade and manage Xerox and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.</p> <ul style="list-style-type: none"> • Printers are automatically discovered • Printer list can be managed based on location • Gives Bi-directional feedback device status, supplies, queue management 		
Print Submission Tools	<ul style="list-style-type: none"> • Command prompt LPR/UNIX tool for print submission • Contents Bridge tool supports TIFF/PDF/XPS and Office 2007 direct print 		
Device Management			
Management Support	SNMP Version 1, SNMP Version 2c and Version 3 trap over TCP/IP and IP MIB access (IETF-MIB II RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v. 2		
Xerox CentreWare® Web	<ul style="list-style-type: none"> • A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system • Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management 		
IP Filter	Allows administrator to control print access to device via IP address.		
Xerox CentreWare® for Unicenter TNG®	<ul style="list-style-type: none"> • Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the device under a Unicenter TNG Business Process View • Provides full integration with event management and the choice to integrate with problem management and advanced Help Desk 		

* Enhanced: Xerox custom graphical user interface

** Standard: Driver based on Microsoft tree structure user interface (includes Xerox features and functionality)

<p>Xerox CentreWare® for Tivoli® NetView®</p>	<ul style="list-style-type: none"> • Provides for the identification of Xerox WorkCentre multifunction printers in the general discovery performed by Tivoli NetView • Provides the ability to see the discovered Xerox printers/devices in a Xerox Printers Set in addition to the Printers SmartSet • Provides full integration with the NetView and Event Browser and Tivoli Enterprise Console (TEC)
<p>Xerox CentreWare® for Microsoft Management Console (MMC)</p>	<p>CentreWare MC Snap-in supports printer discovery and management via a Microsoft Management Console (MMC) link to an embedded Web server. It is a general-purpose management display framework for hosting administrative tools.</p>
<p>Xerox CentreWare® for HP® OpenView®</p>	<ul style="list-style-type: none"> • Provides for the identification of Xerox WorkCentre multifunction printers in the general discovery performed by HP OpenView • Provides the ability to see the current status of discovered Xerox printers/devices under a Xerox PrinterMap and IP Map via color-coded icons • Provides traps and message updates to the OpenView alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView
<p>Xerox Device Manager</p>	<p>Xerox Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox Device Manager provides:</p> <ul style="list-style-type: none"> • Device monitoring and troubleshooting • Extensive reporting and discovery of new devices • Usage collection, chargeback, and billing capabilities
<p>Xerox Device Types for SAP R/3 Environment <i>Information available at www.xeroxofficesap.com</i></p>	<p>Simplifies printing in SAP R/3 environments by providing users of SAP R/3 v4.6C, 4.x and 3.x ERP applications with enhanced WorkCentre printing functionality (PostScript and PCL):</p> <ul style="list-style-type: none"> • Simplex or duplex printing • Finishing – single or dual stapling • Tray pull location from any tray • Print security via PIN ID capability at the WorkCentre
<p>Xerox SAP R/3 Intelligent Barcode Utility (Optional) <i>Information available at www.xeroxofficesap.com</i></p>	<p>Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.x (or higher) network. Used in conjunction with Xerox Device Types for SAP R/3 Environment and Xerox Font Center Barcode Fonts. Utility automatically calculates checksum, placement of start/stop characters, and encoding of data string Web server embedded on SMart network controller</p> <ul style="list-style-type: none"> • Tray status/contents • Consumables status
<p>Xerox Barcode Pro PS <i>Information available at www.xeroxofficesap.com</i></p>	<p>Enables intelligent PostScript printing on Xerox multifunction printers by storing Xerox software as well as the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.</p>
<p>Smart eSolutions</p>	
<p>MeterAssistant</p>	<p>Automates the process of collecting and submitting meter reads for tracking and billing of Xerox device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time. Device Direct or via Smart eSolutions Client for Windows or via CentreWare Web.</p>
<p>SuppliesAssistant</p>	<p>Automatically orders supplies for Xerox output devices based on actual usage, eliminating the need to manually manage supplies inventory. Device Direct or via Smart eSolutions Client for Windows or via CentreWare Web.</p>
<p>Maintenance Assistant</p>	<p>Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime. Device Direct</p>
<p>CentreWare® Internet Services – Integrated Device Web Page</p>	
<p>Device Status</p>	<p>Web server embedded on SMart Network Controller™</p> <ul style="list-style-type: none"> • Tray status/contents • Consumables status

WorkCentre 7425 / 7428 / 7435

Print Queue Viewing	Complete job print queue management – hold, release, promote and delete
Job Submission	Print-ready files (PS, PCL, TIFF, PDF, XPS) Output feature selection
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Windows® XP: Netscape Navigator®, Firefox® Microsoft® Internet Explorer Macintosh® 9.x/OS X: Netscape Navigator® 6.x, Apple® Safari™, Firefox® Linux: Netscape® 6.x
EFI Fiery Network Controller (Optional)	
Processor	1.86 GHz
Memory (ESS)	512 MB
System Disk	80 GB minimum
Print Languages (PDL)	PostScript 3
Features	Command WorkStation capability via a PC or MAC (customer to provide) with Queue Management <ul style="list-style-type: none"> • Job Preview • Job Merge • Change Job Properties Pantone Color Tables Expert Color Settings: Profile, Rendering and Simulation ColorWise Pro Tools – calibration support, color editor, profile manager FreeForm – Variable Data capabilities Booklet Maker 3.0 – booklet wizard to create booklets Print from USB flash drive Microsoft Office Doc conversion – print .doc, .xls, .ppt files without application
Connectivity	Ethernet 10/100/1000BaseTX
Optional	Hot folders and virtual printers Impose 2.7 – imposition Paper Catalog Spot On Color Management Auto Trapping
Fax Specifications	
Network Fax Server Integration (Optional)	
Fax Send Features	One-sided, two-sided, or two-sided rotate side 2 Phone number entry Add to send list (50 numbers maximum) Delay send (specific time) Resolution selection (super fine/600 x 600, super fine/400 x 400, fine/200 x 200, standard/200 x 100 dpi) Original type (photo, text, or photo and text)
Fax Print Features	One- or two-sided printing Quantity Staple on/off Collate on/off Finisher output tray selection (top tray or main tray) Secure print on/off
Fax Vendors	Multiple vendors, certified by the Xerox Alliance Partner Program For details, visit www.xerox.com

Fax (Optional) – Standard with One or Three Line Fax Option	
	ITY (CCITT) group 3 quality/resolution superfine/600x600, super fine/400 x 400, fine/200x200, standard/200x100 dpi
Speed/Modem(s)	V.34 modem(s): 33,600 bps. Less than four seconds per page transmission time. ISDN via third-party adapter.
Speed/Compression	MH/G3, MMR/G4, JBig Super G3
Fax Send Features	<ul style="list-style-type: none"> Fax from print driver Auto fax transmission reduction Page-by-page job status at the machine Fax from platen Delay start Automatic memory resend Automatic cover sheets Priority send Broadcast Booklet Scan PSTN Fax Internet Fax LAN Fax
Fax Receive Features	<ul style="list-style-type: none"> One- or two-sided printing Reduction at reception to fit available paper Junk Fax prevention
Fax Forward	When enabled with the scan and fax kit, faxes can be received into a folder on the device hard drive. Images that are in the folder can be routed to an Email, an FTP or SMB location or a Fax.
Fax Reports	<ul style="list-style-type: none"> Activity report Address Book Transmission confirmation Pending fax Folder List
Fax Receive Mailboxes	Up to 200 password-protected folders
Auto Dialing	Auto redial, Batch send
Single Line option	<ul style="list-style-type: none"> Total of 200 speed dials (single-line option) Up to 50 dial groups with up to 20 recipients per group (single line option) Up to 200 dial groups with up to 200 recipients per group (with extended memory option)
Internet Fax (Optional) – Standard with One or Three Line Fax Option	
Capability	<ul style="list-style-type: none"> Direct document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents in black and white sent via email from remote Internet Fax machines or email clients
Maximum Scan Area	11 x 17 in./A3
Address Directory Access	Downloaded address list (comma-separated value file format)
File Formats	TIFF-FX Profiles S with G3 MH, F with G4 MMR, or J with JBIG
Resolutions	<ul style="list-style-type: none"> 600 x 600 dpi 400 x 400 dpi 200 x 200 dpi 200 x 100 dpi Bit Depth: 1 bit (monochrome)
Network Protocols	<ul style="list-style-type: none"> SMTP POP3
Compliance	ITU-T T.37 compliant

WorkCentre 7425 / 7428 / 7435

Scan Specifications	
Scan to Email (Standard)	
Capability	Color scanning, Auto Color, Grayscale, Black and White Direct document email from device Manual or directory Exchange/Notes/LDAP address searching
Network Protocol	SMTP, S/MIME, LDAP, LDAPs encoded
Authentication	Device login with network user name and password Supports: Kerberos (UNIX/Windows 2003 Server), SMB, (Windows 2003 Server) LDAP Domino
Directory Access	Corporate address list via LDAPv3 Downloaded address list (comma-separated file format)
Scan to Folder (Standard)	
Capability	Color, Auto Color, Black and White
Features	Images can be scanned, printed and faxed directly to the device hard drive and stored in a mailbox. Scan or fax images that are stored in the mailbox can then be printed, emailed, sent via fax, sent via IFax, routed to a PC, an FTP or SMB site via Job Flow Sheets.
Network Scanning (Optional)	
Capability	Color Scanning, Grayscale, Black and White, Auto Color
Concurrency	Scan while the system is copying, printing or while it is transferring scan to network or fax jobs
Input Speed	Scan at 50 ipm monochrome/45 ipm color (216 x 279 mm/A4 long edge feed)
Resolution	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi Bit depth: 1 bit (monochrome), 8 bit (grayscale), 24 bit (color)
Maximum Scan Area	11.7 x 17 in./297 x 432 mm
Secure Access and Authentication	Optional secure device login with network user name and password Supports: Kerberos (Windows UNIX/Windows Server 2003), SMB (Windows Server 2003/Vista) LDAP
Network Protocol	FTP via TCP/IP Microsoft SMB via TCP/IP Netware, HTTP and HTTPS
File Formats	TIFF 6.0 or TTF2 with JPEG, G3MH, G4 MMR compression (single page or multiple pages) PDF, PDF/A with MRC, JPEG, G3 MH, G4 MMR, MRC, JBIG 2 Huffman, JBIG Arithmetic Compression JPEG XPS Searchable PDF, PDF/A, XPS Password Protected PDF Encrypted PDF Linearized PDF
Document Management Fields	One to six user-programmable metadata fields per scan job Customized fields viewed on user interface Variable data entered using virtual keyboard

WorkCentre 7425 / 7428 / 7435

Scan Features	Mixed size originals Bound originals Edge erase Reduction/enlargement Fit to size Scan Build Job Compression Quality/File Size Control Original type (photo and text, photo, text) Auto Background and Shadow Suppression Job Flow Sheets Thumbnail Preview
Supported Scan Destinations (Varies by scanning software options purchased.)	Scan to network server Scan to remote email destinations via direct SMTP addresses or via various network scanning software options Scan to application (Electronic Document Management System/Repositories) Scan to Microsoft Exchange 2000 Web Folders Scan to PC Desktop™ (Professional and SE editions) SMARTsend™ ScanFlowStore™ Scan to Windows XP client SMB or FTP Scan to Folder Scan to Home
Scan to PC Desktop SE	<ul style="list-style-type: none"> • A desktop and server-based offering that provides document imaging, archiving, editing and organization tools • ScanSoft PaperPort – image viewing and file management software • ScanSoft OmniPage (for desktop/client installation) – OCR and file format conversion software • Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops.
Scan to PC Desktop Pro	<ul style="list-style-type: none"> • A desktop and server-based offering that provides document imaging, archiving, editing and organization tools • The PaperPort Personal Scanning Platform empowers office workers with the ability to customize, directly from the desktop, the scanning menus available to them on Xerox EIP enabled MFP devices. • ScanSoft PaperPort Pro – image viewing and file management software • ScanSoft OmniPage Pro (for desktop/client installation) – OCR and file format conversion software • Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox or through email WorkCentre to individual desktops. Also includes an Email inbox polling capability.
Common Access Card Enablement (optional)	Common Access Card Enablement is a solution that increases security of government facilities and critical information through the use of smart identification cards. (Available only in U.S.)
Thumbnail Preview (Optional)	
	Images that are stored in the folder on the device hard drive can be viewed at the User Interface.
Device Specifications	
Security	
Capability	Secure Print, NDS Authentication over IP, LDAP/Kerberos/SMB, Password Protected PDF, Encrypted Disk, Audit Log and Encrypted Scan to Email. Hard disk overwrite immediate or on demand. Secure Web Page via SSL. IPv6
Optional	Secure Watermark, Common Access Card, Secure Access Unified ID System® USB card reader
Accounting	
Accounting with Third-Party Server Applications (optional)	Up-to-the-minute data on how the system is being used; comprehensive usage tracking and reporting; print, scan, copy and fax
Auditron	Controls and tracks black and color copy, print, fax and scan usage

WorkCentre 7425 / 7428 / 7435

Accounting Control	Xerox Standard Accounting Job based accounting Third-party integration Supports Foreign Device Interface Active directory user profile – Controls color copy and print usage Xerox Page Accountant Print Audit 5		
Accounting – Xerox Standard Accounting			
Tracking	Copy, Print, Fax and Scan usage		
Accounting	Up to 1,000 User accounts (User ID); Up to 500 General accounts (Client); Up to 750 Group accounts (Department)		
Features	Enable/disable via the web UI or the GUI in tools, admin can manage the feature remotely via the web UI, Data can be exported via a CSV file, user required to enter XSA ID into the print driver when submitting a print job, similar to secure print.		
	WorkCentre 7425	WorkCentre 7428	WorkCentre 7435
Monthly Duty Cycle			
	60,000	80,000	105,000
Basic Configurations***			
	Network Multifunction System with network controller – Copy and Print capability standard		
Accessories			
	Three Tray Paper Feeder High Capacity Tandem Tray High Capacity Feeder One-line fax with Internet Fax Three-line fax with Internet Fax Fax Server Enablement Scan Kit Thumbnail preview Secure Watermark Scan to PC Desktop (Professional or SE edition) Media Print (Print from a USB Thumb drive or media card) (includes Work Surface) USB/Parallel Port Printing Integrated Office Finisher Office Finisher LX Booklet Maker (requires Office Finisher LX) Professional Finisher Foreign Device Interface Convenience Stapler (includes Work Surface)		
Electrical Requirements			
	220–240 V Nominal, 50/60 Hz, 10A 100-127 Vac, 50/60 Hz, 12A		
Power Consumption			
Running	< 646 watts		
Standby	< 145 watts		
Low-Power Mode	< 79 watts		
Sleep Mode	< 2 watts		
Warm Up	45 seconds (maximum)		

WorkCentre 7425 / 7428 / 7435

Low-Power Recovery	30 seconds (maximum)			
Required Temperature Range	50° to 82° F (10° to 28° C)			
Required Relative Humidity	15 % to 85 %			
Noise Emission	20 dB(A) standby 56 dB(A) running			
Heat Emission	2584 BTU/Hr running 580 BTU/Hr standby			
Dimensions and Weights	Width	Depth	Height	Weight
Base Unit	41.2 in. / 1046 mm	26.6 in. / 678 mm	44.3 in. / 1125 mm	317.5 lbs / 144 kg
Xerox Extensible Interface Platform™ (EIP)				
	Xerox EIP is a software platform inside the WorkCentre 7425/7428/7435 that enables personalized solutions you can access right from the device touch screen. These applications can leverage your existing databases and meet your specific business challenges.			
Certifications				
	FCC Class B Compliant (U.S./Canada) EnergyStar 89/336/EEC (Europe) TUV Listed CB Certified (IEC 60950-1/EN 60950-1) 73/23/EEC (Europe) Novell Tested and Approved Windows Hardware Quality Labs			
Supplies	Description	Order Number		
Toner Cartridges	Black Toner Cartridge - Metered	006R01391		
	Yellow Toner Cartridge - Metered	006R01392		
	Magenta Toner Cartridge - Metered	006R01393		
	Cyan Toner Cartridge - Metered	006R01394		
	Black Toner Cartridge - Sold	006R01395		
	Yellow Toner Cartridge - Sold	006R01396		
	Magenta Toner Cartridge - Sold	006R01397		
	Cyan Toner Cartridge - Sold	006R01398		
Staple Refills	Integrated Office Finisher	008R12941		
	Office Finisher LX	008R12941		
	Professional Finisher	008R12941		

WorkCentre 7425 / 7428 / 7435

Staple Cartridges	Integrated Office Finisher	008R12964
	Office Finisher LX	008R12964
	Professional Finisher	008R12964
	Booklet Maker for Office Finisher LX	008R12897
	Booklet Maker for Professional Finisher	008R12925
SMart Kits	Description	Order Number
	SMart Kit™ Drum Cartridge	013R00647
	SMart Kit™ Waste Cartridge	008R13061
	SMart Kit™ Fuser Module (220 V)	008R13063
	SMart Kit™ Fuser Module (110 V)	008R13062
	Intermediate Belt Transfer Cleaner	001R00600
	Belt Transfer Roller	008R13064

